

**KWVE30-B-H**

Recirculating ball bearing carriage

Carriages KWVE...-B-H, high, narrow carriage, four-row

Teknik bilgiler







Mevcut ürün modeliniz

Size code	30	
Version	B	
Carriage design	H	High carriage

Main Dimensions & Performance Data

H	45 mm	Height system
B	60 mm	Width carriage
L	99 mm	Overall length carriage
C	27.500 N	Dynamic load rating
C ₀	55.000 N	Static load rating
M _{0x}	970 Nm	Static moment rating about X axis
M _{0y}	700 Nm	Static moment rating about Y axis
M _{0z}	700 Nm	Static moment rating about Z axis
≈m	1,04 kg	Ağırlık



Mounting dimensions

A ₁	16 mm	Distance from locating edge on carriage to locating edge on guideway
J _B	40 mm	
b	28 mm	Width rail
A ₂	10 mm	Distance from locating edge to hole
L ₁	72 mm	
L _S	1,65 mm	
J _L	40 mm	
H ₁	5,9 mm	Free space, system dimension
H ₅	6,25 mm	
T ₅	13,5 mm	Thread depth
G ₂	M8	Fixing screws above (DIN ISO 4762-12.9)
G ₂ M _A	41 Nm	Maximum tightening torque
A ₃	14,5 mm	Position lubrication connector
G ₃	M6	Lubrication connector
t _{G3}	7 mm	Maximum permissible screw depth for lubrication connectors
A ₄	10 mm	Position lubrication connector
G ₄	M6	Lubrication connector
t _{G4}	7 mm	Maximum permissible screw depth for lubrication connectors
J _{L6}	21,5 mm	Position lubrication connector

Additional information

VMKB_065	KWVE	Material name
----------	------	---------------