



KWVE35-B-SN

Recirculating ball bearing carriage

Carriages KWVE...-B-SN, narrow, low carriage, four-row

Teknik bilgiler







Mevcut ürün modeliniz

Size code	35	
Version	B	
Carriage design	SN	Narrow, low carriage

Main Dimensions & Performance Data

H	44 mm	Height system
B	70 mm	Width carriage
L	112 mm	Overall length carriage
C	38.000 N	Dynamic load rating
C ₀	72.000 N	Static load rating
M _{0x}	1.465 Nm	Static moment rating about X axis
M _{0y}	1.020 Nm	Static moment rating about Y axis
M _{0z}	1.020 Nm	Static moment rating about Z axis
≈m	1,24 kg	Ağırlık



Mounting dimensions

A 1	18 mm	Distance from locating edge on carriage to locating edge on guideway
J B	50 mm	
b	34 mm	Width rail
A 2	10 mm	Distance from locating edge to hole
L 1	80 mm	
L S	1,65 mm	
J L	50 mm	
H 1	6,7 mm	Free space, system dimension
H 5	6,75 mm	
T 5	13,5 mm	Thread depth
G 2	M8	Fixing screws above (DIN ISO 4762-12.9)
G2 M A	41 Nm	Maximum tightening torque
A 3	8,3 mm	Position lubrication connector
G 3	M6	Lubrication connector
t G 3	7 mm	Maximum permissible screw depth for lubrication connectors
A 4	7 mm	Position lubrication connector
G 4	M6	Lubrication connector
t G 4	7 mm	Maximum permissible screw depth for lubrication connectors
J L6	22 mm	Position lubrication connector

Additional information

VMKB_065	KWVE	Material name
----------	------	---------------